



Schrumpf Klemring voor afdichtingen van mantelbuizen en boorgaten



kernboorgat	Type	Buis in mm	gewicht
		minimaal - maximaal	kg
50	S-0080	6 mm – 12 mm	0,38
80	S-0100	20 mm – 28 mm	0,41
80	S-0105	32 mm – 40 mm	0,42
80	S-0095	48 mm – 50 mm	0,41
100	S-01-7	15 mm – 22 mm	0,59
100	S-0110	20 mm – 28 mm	0,59
100	S-0112	25 mm – 32 mm	0,59
100	S-0115	32 mm – 40 mm	0,64
100	S-0120	36 mm – 44 mm	0,64
100	S-0125	46 mm – 56 mm	0,54
100	S-0130	55 mm – 65 mm	0,52
125	S-0140	45 mm – 54 mm	1,05
125	S-0145	55 mm – 64 mm	0,84
125	S-0150	70 mm – 78 mm	0,75
150	S-0152	46 mm – 54 mm	1,37
150	S-0153	56 mm – 66 mm	1,32
150	S-1055	69 mm – 78 mm	1,22
150	S-0160	79 mm – 91 mm	1,18
150	S-0165	85 mm – 94 mm	1,07
150	S-0170	98 mm – 110 mm	0,96
200	S-0172	88 mm – 103 mm	2,00
200	S-0175	108 mm – 115 mm	1,96
200	S-0180	116 mm – 126 mm	1,88
200	S-0185	132 mm – 141 mm	1,63
200	S-0190	135 mm – 144 mm	1,46
200	S-0192	150 mm – 160 mm	1,40
250	S-0195	135 mm - 144 mm	2,90
250	S-0197	140 mm – 149 mm	2,90
250	S-0200	150 mm – 159 mm	2,60
250	S-0205	157 mm – 162 mm	2,60
250	S-0210	174 mm – 181 mm	2,55
250	S-0215	178 mm – 187 mm	2,15
250	S-0216	197 mm – 202 mm	2,10
250	S-0218	204 mm – 210 mm	2,05
300	S-0225	193 mm – 204 mm	3,50
300	S-0230	218 mm – 226 mm	3,15
350	S-0235	224 mm – 233 mm	5,25
350	S-0240	249 mm – 258 mm	4,85
350	S-0242	270 mm – 282 mm	4,55
400	S-0245	270 mm – 280 mm	5,70
400	S-0250	279 mm – 288 mm	5,65
400	S-0255	304 mm – 313 mm	5,10
400	S-0260	314 mm – 323 mm	4,60
400	S-0265	320 mm – 330 mm	4,20

